

SHRE®

SHRE®

AN ISO 9001:2015 CERTIFIED COMPANY
Automatic Water Pressure Pumps

FEEL THE
PRESSURE



PARAS ENGINEERING WORKS

Factory:

Plot No 19-20 /188 G.I.D.C. Chitra,
Bhavnagar, Gujarat 364 001
Tel : 0278-2515412 | Enquiry No. +91 96871 68686

Head Office:

Plot No. 190, 1-4 Ghodbunder Village Road,
Off. Western Express Highway, Mira Road (East),
Thane - 401 107 | Enquiry No.: +91 99877 88185

Display Center:

Shop No. 10/11, Riddhi Siddhi Building, Near S.T. Depot,
M. G. Road. Borivali (East) Mumbai- 400 091
Enquiry No.: +91 90291 74441

Service Centers :

Mumbai -
Mira road, Jogeshwari, Ghatkopar,
Nallasopara, Masjid bundar, Thane, Turbhe

Pune - Sukrawar peth
Nagpur - Geeta Mandir Complex
Bhavnagar - GIDC Chitra
Surat - Station Road
Vadodara - laheripura
Ahmedabad - Relief Road
Hydrabad - Rani Gunj
Bangalore - SJP Road

PRIZM ART 72088 37322



POWER
SAVING



WWW.SHREPRESSUREPUMPS.COM

Paras Engineering Works has been in the field of manufacturing since 45 years , it has brand name SHRE®

We manufacturing reverse osmosis water plant , membrane test kit machine and many specialized machine for membrane development and production works with a dedicated team of specialist with high infrastructure and latest machinery.

We also Manufacture and import automatic water pressure pump with best quality.

SHRE® also export some of it's product to the worlds corner in commercial and industrial sector.

Team of SHRE® is always endeavour to satisfy their customers ever widening in demands.

 WWW.SHREPRESSUREPUMPS.COM



Contents

- CIRCULATING PUMP SERIES
- SELF-PRIMING PRESSURE PUMP SERIES
- MULTISTAGE SUPER SILENT PRESSURE PUMP SERIES
- SELF-PRIMING REGENERATIVE PUMP SERIES
- CENTRIFUGAL OPENWELL SUBMERSIBLE PUMP SERIES
- HIGH PRESSURE WASHER

Follow us on :



CIRCULATING PUMP SERIES

R 120



120 W

M.R.P. - ₹ 6,300/-

R 250




250 W

M.R.P. - ₹ 7,300/-

Feature:

- 1. Super Silent
- 2. Compact Design
- 3. Ideal For Continuous Running Water
- 4. In Absence Of Electricity The Flow Of Water Remains Same
- 5. Long Lasting Quality - Zero Maintenance
- 6. Maximum Liquid Temperature: +0~+80C



TECHNICAL DATA

MODEL	POWER (HP / W)	MAX FLOW (L.MIN)	PIPE SIZE (M)	RPM
R 120	120 W	25	3/4"	2,850
R 250	250 W	35	3/4"	2,850

Suitable for any One function at a time
(Bathroom Tap, Small Shower, Geyser)

R 120 : Shower up to 4" x 4"

R 250 : Shower up to 6" x 6" | Water Purifier



R 350




350 W

M.R.P. - ₹ 11,700/-

Feature:

- 1. Super Silent
- 2. Compact Design
- 3. Ideal For Continuous Running Water
- 4. In Absence Of Electricity The Flow Of Water Remains Same
- 5. Long Lasting Quality - Zero Maintenance
- 6. Maximum Liquid Temperature: +0~+80C



TECHNICAL DATA

MODEL	POWER (HP / W)	MAX FLOW (L.MIN)	PIPE SIZE (M)	RPM
R 350	350 W	45	3/4"	2,850



WASHING MACHINE



WATER PURIFIER



SHOWER



GEYSER

USAGES OF PUMP

- A) Suitable for any 2 - 3 function at a time
(Bathroom Tap, Small Shower, Geyser)
- B) Shower up to 8" x 8"
- C) Automatic washing machine use



POWER 2

0.25 HP

M.R.P. - ₹ 8,900/-




SUITABLE FOR ONE BATHROOM

Feature:
Light weight and compact design
The automatic pressure system is designed to automatically start & Stop the pump on opening and closing of taps.

Application:
Suitable For water supply in Flats, Salon, Hotel, Restaurants & Corporate.

Technical Specification:
Maximum Liquid Temperature: +0~+80C
Copper Winding
Brass Impeller
Premium Quality Pressure Tank
Shaft: Stainless steel AISI 410
TOP - Thermal Overload Protector



High Efficiency and Energy saving Design

TECHNICAL DATA

MODEL	POWER	H. MAX	Q. MAX	PIPE SIZE	PRESSURE	TANK
	(HP / W)	(M)	(L.MIN)	(M)	(BAR)	(L)
POWER 2	0.25 HP	22	24	1/2" X 1/2"	2.2	1



USAGES OF PUMP

- Suitable for 1 BATHROOM (any one combination)
- A) 2 or 3 connection at a time
(Taps | Shower | Geyser | Health Faucet | Flush Tank | Kitchen Faucet)
 - B) Shower up to 6" x 6"
 - C) Automatic washing machine use

IDEAL FOR



WASHING MACHINE



FAUCET



SHOWER



GEYSER

POWER 2 PLUS

0.35 HP

M.R.P. - ₹ 10,300/-



SUITABLE FOR ONE BATHROOM
(with High Performance)




Feature:
Light weight and compact design
The automatic pressure system is designed to automatically start & Stop the pump on opening and closing of taps.

Application:
Suitable For water supply in Flats, Salon, Hotel, Restaurants & Corporate.

Technical Specification:
Maximum Liquid Temperature: +0~+80C
Copper Winding
Brass Impeller
Premium Quality Pressure Tank
Shaft: Stainless steel AISI 410
TOP - Thermal Overload Protector

High Efficiency and Energy saving Design



TECHNICAL DATA

MODEL	POWER (HP / W)	H. MAX (M)	Q. MAX (L.MIN)	PIPE SIZE (M)	PRESSURE (BAR)	TANK (L)
POWER 2+	0.35 HP	28	30	1"X 1"	2.5	1



USAGES OF PUMP

- Suitable for 1 Bathrooms (With High Performance)
- A) 2 or 3 connection at a time
(Taps | Shower | Geyser | Health Faucet | Flush Tank | Kitchen Faucet)
 - B) Shower up to 9" x 9"
 - C) Automatic washing machine use

IDEAL FOR



FAUCET



SHOWER



WASHING MACHINE



GEYSER



DISH WASHER

POWER 3

0.5 HP

M.R.P. - ₹ 11,700/-




SUITABLE FOR TWO BATHROOM

Feature:
Light weight and compact design
The automatic pressure system is designed to automatically start & Stop the pump on opening and closing of taps.

Application:
Suitable For water supply in Flats, Salon, Hotel, Restaurants & Corporate.

Technical Specification:
Maximum Liquid Temperature: +0~+80C
Copper Winding
Brass Impeller
Premium Quality Pressure Tank
Shaft: Stainless steel AISI 410
TOP - Thermal Overload Protector



High Efficiency and Energy saving Design

TECHNICAL DATA						
MODEL	POWER	H. MAX	Q. MAX	PIPE SIZE	PRESSURE	TANK
	(HP / W)	(M)	(L.MIN)	(M)	(BAR)	(L)
POWER 3	0.5 HP	38	40	1"X 1"	3.5	1.5



USAGES OF PUMP

Suitable for 2 Bathrooms at a time (any one combination)

- A) 3 or 4 connection at a time
(Taps | Shower | Geyser | Washing Machine | Sink Faucet | Dish Washer)
- B) Single Rain Shower up to 12" x 12"
- C) 2 Showers up to 6" x 6"
- D) Shower Panel
- E) 4 Pcs. Body Jets 2" x 2"

POWER 4

1.0 HP

M.R.P. - ₹ 20,800/-



SUITABLE FOR
BODY JET | BATHTUB
SHOWER PANEL | BIG SIZE SHOWER

SUITABLE FOR 3 to 4 Bathroom

Feature:
Light weight and compact design
The automatic pressure system is designed to automatically start & Stop the pump on opening and closing of taps.


Application:
Suitable For water supply in Flats, Salon, Hotel, Restaurants & Corporate.

Technical Specification:
Maximum Liquid Temperature: +0~+80C
Copper Winding | Brass Impeller | Premium Quality Pressure Tank
Shaft: Stainless steel AISI 410 | TOP - Thermal Overload Protector

High Efficiency and Energy saving Design


USAGES OF PUMP

- A) 4 or 5 connection at a time
- B) Single Rain Shower up to 16" x 16"
- C) 3 Showers up to 6" x 6"
- D) Shower Panel | Body Jets (2" x 2" 6 Jets)
- E) 4 Pcs. Body Showers 4" x 4"



TECHNICAL DATA

MODEL	POWER (HP / W)	H. MAX (M)	Q. MAX (L.MIN)	PIPE SIZE (M)	PRESSURE (BAR)	TANK (L)
POWER 4	1 HP	55	58	1"X 1"	5.5	2
POWER 8	1.5 HP	65	90	1.5"X 1.5"	6.5	2.5
POWER 9	2.0 HP	75	125	1.5"X 1.5"	7.5	2.5



1 HP
SUITABLE FOR
3 to 4 Bathroom



1.5 HP
SUITABLE FOR
4 to 5 Bathroom



2 HP
SUITABLE FOR
5 to 6 Bathroom



POWER 5

0.5 HP

M.R.P. - ₹ 23,000/-

POWER 6

0.75 HP


M.R.P. - ₹ 27,000/-



POWER 7

1.0 HP

M.R.P. - ₹ 33,000/-



USAGES OF PUMP

For Commercial, Industrial And Residential Use

Suitable for 2 or 3 Bathrooms

(Taps | Shower | Geyser | Washing Machine | Sink Faucet)

A) Single / Multi Function Ceiling Shower up to 16" X 16"

B) Shower Panel | Body Jets | Body Shower



FEATURES

Noiseless Pump | Wear Resistance Stainless Steel

Dry Run Protection | Thermal Overload Protected

Long Life | Low Maintenance



TECHNICAL DATA

MODEL	POWER (HP / W)	PIPE SIZE (M)	PRESSURE (BAR)	WATER FLOW			
				HEAD	LPM	HEAD	LPM
POWER 5	0.5 HP	1" X 1"	3.5	6	60 Ltr.	12	40 Ltr.
POWER 6	0.75 HP	1" X 1"	4.5	6	80 Ltr.	12	60 Ltr.
POWER 7	1.0 HP	1" X 1"	5.5	6	100 Ltr.	12	80 Ltr.



POWER 10

1.5 HP

M.R.P. - ₹ 49,000/-

Ideal For Bungalow & Villas having
4 to 5 Bathrooms with
Individual Overhead tank

POWER 11

2.0 HP

M.R.P. - ₹ 59,000/-

Ideal For Bungalow & Villas having
5 to 6 Bathrooms with
Individual Overhead tank



USAGES OF PUMP

For Commercial, Industrial And Residential Use

- A) Single / Multi Function Ceiling Shower up to 24" X 24"
- B) Shower Panel | Body Jets | Body Shower | Bath Tub
- C) Suitable for Villas, Hotels, Gym, Resort, Mall etc.



FEATURES

Noiseless Pump | Wear Resistance Stainless Steel
Dry Run Protection | Thermal Overload Protected
Long Life | Low Maintenance



TECHNICAL DATA

MODEL	POWER (HP / W)	PIPE SIZE (M)	PRESSURE (BAR)	WATER FLOW			
				HEAD	LPM	HEAD	LPM
POWER 10	1.5 HP	1" X 1"	6.5	6	120 Ltr.	12	100 Ltr.
POWER 11	2.0 HP	1" X 1"	7.5	6	140 Ltr.	12	120 Ltr.



POWER 12

2.5 HP

M.R.P. - ₹ 71,000/-

Ideal For Bungalow & Villas having
7 to 8 Bathrooms with
Individual Overhead tank



POWER 13

3.0 HP

M.R.P. - ₹ 85,000/-

Ideal For Bungalow & Villas having
9 to 10 Bathrooms with
Individual Overhead tank



USAGES OF PUMP

For Commercial, Industrial And Residential Use

- A) Single / Multi Function Ceiling Shower up to 30" X 30"
- B) Shower Panel | Body Jets | Body Shower | Bath Tub
- C) Suitable for Villas, Hotels, Gym, Resort, Mall etc.



FEATURES

Noiseless Pump | Wear Resistance Stainless Steel
Dry Run Protection | Thermal Overload Protected
Long Life | Low Maintenance



TECHNICAL DATA

MODEL	POWER (HP / W)	PIPE SIZE (M)	PRESSURE (BAR)	WATER FLOW			
				HEAD	LPM	HEAD	LPM
POWER 12	2.5 HP	1" X 1"	7.5	6	160 Ltr.	12	140 Ltr.
POWER 13	3.0 HP	1" X 1"	8.5	6	180 Ltr.	12	160 Ltr.

SELF PRIMING REGENERATIVE PUMP



POWER GOLD SERIES

HP	M.R.P.
0.5	6,300
1.0	9,700
1.5	15,700
2.0	20,900



Applications :

- Water Supply to Residential Bungalows, Garages, Flats, Laundries, Hospitals, Hotels, Resorts, Commercial Places etc.
- Water Feeding in solar systems.
- Ornamental Fountains.
- Gardening.
- Lawn Sprinklers.



Instant Suction, Up to 9 Meters



Suitable for Wide Voltage Application



Easy for Maintenance

Technical Specifications :

- Range : 0.5 HP to 2 HP
- Rated Voltage : 220V
- Rated Frequency : 50Hz
- Max. Head : Up to 45 Meters.
- Max. Discharge : 4550 LPH.
- Liquid : Clear & Cold Water.
- Single Phase



SS304 Suction & Delivery Casing for Stuck Free & Rust free operation




High Quality Forged Brass Impeller for longer Life

TECHNICAL DATA

MODEL	POWER (HP)	PIPE SIZE (MM)	DISCHARGE IN LPH (HEAD IN METER)						
			6M	12M	18M	24M	30M	36M	45M
POWER GOLD - 50	0.5 HP	15 x 15	1300	1100	800	550			
POWER GOLD - 100	1.0 HP	25 x 25	2150	1850	1500	1400	1050		
POWER GOLD - 150	1.5 HP	25 x 25	3350	3050	2750	2350	1950	1750	1250
POWER GOLD - 200	2.0 HP	25 x 25	4550	4050	3650	3250	2850	2450	1850

CENTRIFUGAL OPENWELL SUBMERSIBLE PUMPS



OPENWELL SERIES

HP	M.R.P.
0.5	10,800
1.0	16,800
2.0	31,000
3.0	37,000
5.0	47,000
7.5	53,000



Features :

- Single Phase
- High Thrust Capacity
- Pre-filled with Coolant
- Anti-Rust CED Coating
- Wide Voltage Application
- High Grade Electrical Stamping
- Easy for Maintenance



Ideal for Water Transfer from underground tank to overhead tank, Gardening, Water Fountain, Agriculture, Irrigation, Domestic Water supply in Hotels, Buildings and Apartments.

TECHNICAL DATA

MODEL	POWER (HP)	HEAD (METER)	HEAD (FEET)	DISCHARGE (LPM)
OPENWELL - 50	0.5 HP	09-20	30-66	155-30
OPENWELL - 100	1.0 HP	12-27	40-89	140-10
OPENWELL - 200	2.0 HP	12-30	40-99	320-120
OPENWELL - 300	3.0 HP	8-36	27-118	400-155
OPENWELL - 500	5.0 HP	8-48	27-157	460-200
OPENWELL - 750	7.5 HP	33-57	109-187	630-220

**AUTOMATIC HIGH PRESSURE WASHER
FOR MULTIPURPOSE USE**



FEATURES

FULL BRASS HEAD
INDUCTION MOTOR
FULLY AUTOMATIC OPERATING SYSTEM
ADDITIONAL FOAM WASH OPTION
SELF SUCTION
LOW NOISE

BRUSHLESS MOTOR FOR LONGER LIFE
COMPACT DESIGN
ADJUSTABLE PRESSURE GUN
PORTABLE HANDLING
EASY REPAIRABLE

ACCESSORIES



USAGES



VEHICLE WASH



FOAM WASH



SOLAR PANNEL WASH



A/C CLEANING



WATERING PLANT



FLOOR CLEANING



**Power
1800 WATTS
140 BAR
M.R.P. - ₹ 10,700/-**



**Power
2400 WATTS
180 BAR
M.R.P. - ₹ 11,700/-**



**Power
2800 WATTS
220 BAR
M.R.P. - ₹ 14,700/-**